

Defined Types

EODeleteRule

DECLARED IN EOControl/EOClassDescription.h

SYNOPSIS typedef enum {
 EODeleteRuleNullify = 0,
 EODeleteRuleCascade,
 EODeleteRuleDeny
} **EODeleteRule**;

DESCRIPTION Used by EOClassDescription to specify the delete rule for a relationship. See the EOClassDescription class specification for more information.

EOObserverPriority

DECLARED IN EOControl/EOObserver.h

SYNOPSIS typedef enum {
 EOObserverPriorityImmediate,
 EOObserverPriorityFirst,
 EOObserverPrioritySecond,
 EOObserverPriorityThird,
 EOObserverPriorityFourth,
 EOObserverPriorityFifth,
 EOObserverPrioritySixth,
 EOObserverPriorityLater
} **EOObserverPriority**;

DESCRIPTION Used by EODelayedObservers and EODelayedObserverQueues to specify a priority for receiving notifications. See the specifications for these classes for more information.

Symbolic Constants

Run Loop Orderings

DECLARED IN	EOControl/EOEditingContext.h
SYNOPSIS	EOEditingContextFlushChangesRunLoopOrdering300000
DESCRIPTION	Used by EOEditingContext as the order argument to NSRunLoop's performSelector:target:argument:order:modes: method.
DECLARED IN	EOControl/EUndoManager.h
SYNOPSIS	EUndoManagerCloseGroupingRunLoopOrdering350000
DESCRIPTION	Used by EUndoManager as the order argument to NSRunLoop's performSelector:target:argument:order:modes: method.
DECLARED IN	EOControl/EOObserver.h
SYNOPSIS	EOFlushDelayedObserversRunLoopOrdering400000
DESCRIPTION	Used by EODelayedObserverQueue as the order argument to NSRunLoop's performSelector:target:argument:order:modes: method.

Observer Priorities

DECLARED IN	EOControl/EOObserver.h
SYNOPSIS	EOObserverNumberOfPriorities ((unsigned)EOObserverPriorityLater + 1)

Comparison Selectors

DECLARED IN EOControl/EOQualifier.h

SYNOPSIS	EOQualifierOperatorEqual	@selector(isEqualTo:)
	EOQualifierOperatorNotEqual	@selector(isNotEqualTo:)
	EOQualifierOperatorLessThan	@selector(isLessThan:)
	EOQualifierOperatorGreaterThan	@selector(isGreaterThan:)
	EOQualifierOperatorLessThanOrEqualTo	@selector(isLessThanOrEqualTo:)
	EOQualifierOperatorGreaterThanOrEqualTo	@selector(isGreaterThanOrEqualTo:)
	EOQualifierOperatorContains	@selector(doesContain:)
	EOQualifierOperatorLike	@selector(isLike:)

DESCRIPTION Used to specify a selector to use to compare objects in an EOQualifier. See the EOQualifier class specification for more information.

Sort Ordering Selectors

DECLARED IN EOControl/EOSortOrdering.h

SYNOPSIS	EOCompareAscending	@selector(compareAscending:)
	EOCompareDescending	@selector(compareDescending:)
	EOCompareCaseInsensitiveAscending	@selector(compareCaseInsensitiveAscending:)
	EOCompareCaseInsensitiveDescending	@selector(compareCaseInsensitiveDescending:)

DESCRIPTION Used to specify a selector to use to order objects in an EOSortOrdering. See the EOSortOrdering class specification for more information.

Global Variables

Aggregate Exception Key

DECLARED IN EOControl/EOClassDescription.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOAdditionalExceptionsKey**;

Exception Names

DECLARED IN EOControl/EOClassDescription.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOValidationException**;

Notification Names

DECLARED IN EOControl/EOClassDescription.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOClassDescriptionNeededNotification**;

DECLARED IN EOControl/EOObjectStoreCoordinator.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOCooperatingObjectStoreWasAdded**;
EOCONTROL_EXTERN NSString ***EOCooperatingObjectStoreWasRemoved**;

DECLARED IN EOControl/EOGlobalID.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOGlobalIDChangedNotification**;

DECLARED IN EOControl/EOUndoManager.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOUndoManagerCheckpointNotification;**

DECLARED IN EOControl/EOObjectStore.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOObjectsChangedInStoreNotification;**
EOCONTROL_EXTERN NSString ***EOInvalidatedAllObjectsInStoreNotification;**

DECLARED IN EOControl/EOEditingContext.h

SYNOPSIS EOCONTROL_EXTERN NSString ***EOObjectsChangedInEditingContextNotification;**
EOCONTROL_EXTERN NSString ***EOEditingContextDidSaveChangesNotification;**